This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of creating run time executable code, comprising:

partitioning a processing element array into a plurality of hardware accelerators;

decomposing a program description source code into a plurality of kernel sections for execution on said plurality of hardware accelerators;

mapping said kernel sections into a plurality of hardware dependent designs; and

forming a matrix describing said hardware accelerators and said designs configured to support run time execution of the plurality of kernel sections

- 2. (Original) The method of claim 1, wherein said partitioning includes partitioning into digital signal processors.
- 3. (Original) The method of claim 1, wherein said partitioning includes partitioning into bins.
- 4. (Original) The method of claim 1, wherein said mapping includes mapping into multiple hardware

-2-

5. (Original) The method of claim 4, wherein said mapping into multiple hardware contexts includes mapping a first set of variants.

- 6. (Original) The method of claim 5, wherein said first set of variants are produced based upon resource usage.
- 7. (Original) The method of claim 5, wherein said mapping includes mapping a second set of variants of said designs configured to support multiple hardware configurations of one of a plurality of bins.
- 8. (Original) The method of claim 1, wherein said mapping is performed by a place and route.
- 9. (Original) The method of claim 1, wherein said decomposing is performed manually.
- 10. (Original) The method of claim 1, wherein said decomposing is performed by a software profiler.
- 11. (Original) The method of claim 10, wherein said decomposing includes executing code compiled from said program description and monitoring timing of said executing.
- 12. (Original) The method of claim 11 wherein said executing utilizes a set of test data.

The method of claim 11, wherein said monitoring includes determining functions that consume a significant portion of said timing of said executing.

- 14. (Original) The method of claim 10, wherein said decomposing includes identifying kernel sections by identifying regular structures.
- 15. (Original) The method of claim 10, wherein said decomposing includes identifying kernel sections by identifying sections with a limited number of inputs and outputs.
- 16. (Original) The method of claim 10, wherein said decomposing includes identifying kernel sections by identifying sections with a limited number of branches.
- 17. (Original) The method of claim 10, wherein decomposing identifies overhead sections.
- 18. (Original) The method of claim 1, wherein mapping includes creating microcode.
- 19. (Original) The method of claim 1, wherein said mapping includes creating context dependent configurations.
- 20. (Original) The method of claim 1, wherein said matrix is sparsely-populated.

21. (Original) The method of claim 1, wherein said matrix is fully-populated

- 22. (Currently Amended) A system for creating run time executable code, comprising:
- a plurality of hardware accelerators partitioned from a processing element array;
- a plurality of kernel sections created from a program description source code for execution on said plurality of hardware accelerators;
- a plurality of hardware dependent designs derived from said kernel sections; and
- a matrix describing said hardware accelerators and said designs configured to support run time execution.
- 23. (Original) The system of claim 22, wherein said hardware accelerators includes digital signal processors.
- 24. (Original) The system of claim 22, wherein said hardware accelerators includes bins.
- 25. (Original) The system of claim 24, wherein said bins support multiple hardware contexts.
- 26. (Original) The system of claim 25, wherein said bins support a first set of variants configured to support said multiple hardware contexts.

27. (Original) The system of claim 26, wherein said first set of variants are produced based upon resource usage.

- 28. (original) The system of claim 27, wherein a second set of variants of said designs are configured to support multiple hardware configurations of one of said plurality of bins.
- 29. (Original) The system of claim 22, wherein said mapping is performed by a place and route.
- 30. (Original) The system of claim 22, wherein said decomposing is performed manually.
- 31. (Original) The system of claim 22, wherein said decomposing is performed by a software profiler.
- 32. (Original) The system of claim 31, wherein said software profiler executes code compiled from said program description, and monitors time consumed.
- 33. (Original) The system of claim 32, wherein said software profiler includes a set of test data.
- 34. (Original) The system of claim 32, wherein said software profiler determines functions that consume a significant portion of said time consumed.

35. (Original) The system of claim 31, wherein said software profiler is configured to identify kernel sections by identifying regular structures.

- 36. (Original) The system of claim 31, wherein said software profiler is configured to identify kernel sections by identifying sections with a limited number of inputs and outputs.
- 37. (Original) The system of claim 31, wherein said software profiler is configured to identify kernel sections by identifying sections with a limited number of branches.
- 38. (Original) The system of claim 31, wherein said profiler identifies overhead sections.
- 39. (Original) The system of claim 22, wherein said designs include microcode.
- 40. (Original) The system of claim 39, wherein said microcode includes context dependent configurations.
- 41. (Original) The system of claim 22, wherein said matrix is sparsely-populated.
- 42. (Original) The system of claim 22, wherein said matrix is fully-populated.

(Currently Amended) A machine-readable medium having stored thereon instructions for processing elements, which when executed by said processing elements perform the following:

partitioning a processing element array into a plurality of hardware accelerators;

decomposing a program description source code into a plurality of kernel sections for execution on said plurality of hardware accelerators;

mapping said kernel sections into a plurality of hardware dependent designs; and

forming a matrix describing said hardware accelerators and said designs configured to support run time execution.

44. (Currently Amended) A system configured to create run time executable code, comprising:

means for partitioning a processing element array into a plurality of hardware accelerators;

means for decomposing a program description source code into a plurality of kernel sections for execution on said plurality of hardware accelerators;

means for mapping said kernel sections into a plurality of hardware dependent designs; and

means for forming a matrix describing said hardware accelerators and said designs configured to support run time execution.